

Linospport Classic 4 mm

Data Sheet

Description	Single layer. Homogeneous linoleum floor with jute canvas backing. Classic linofinish in situ applied in PU coating.
Available colours	Green (1844 808), Beige (1844 8 11), Yellow, (1844 830), Orange (1844 841), Blue (1844 865), Sky (1844 868), Grey (1844 869), Rose (1844 880)
Destination	Indoor sports facilities
Sub base	Wood sub base
Thickness	4 mm (EN 428)
Weight	4.80 kg/m ² (EN 430)
Width	2 m (EN 426)
Length (rolls)	28 lm x 2 lm = 56 m ² 56 m ² x 4.80 kg/m ² = 268 kg
Force reduction	Non applicable (EN 14808)
Sliding properties	95 (EN 13036-4) with Linofinish
Cigarette burns	Resistant (EN 1399)
Light resistance	>= 6 (ISO 105 B02 Method 3)
Gloss	15 (NFT 30064) with Linofinish
Antistatic	<2kV (EN 1815)
Fire rating	Euroclass: C _{fi} -S1 (EN 13501-1)
Castor chair	Type W
Warranty	5 years
Maintenance	According to maintenance instructions
Laying instructions	According to laying instructions

We reserve the right to modify these specifications without, however, affecting their compliance with standards