

Lumaflex Pro

Data Sheet

Description	Polyethylene film vapor barrier. Tarfoam 1500 PU foam. Interlocking plywood boards, 20.5mm thick to improve shock absorption. Omnisports Pro floor covering: fibreglass-stabilised vinyl floor covering with PVC foam backing. Sanitized [®] and protected with Top Clean XP [®] .
Destination	Indoor Sports facilities.
Available colours	Orange, black, yellow, red, grey, forest green, field green, royal blue, sky blue, Teal, Maple, Beech, Oak classic, oak gunstock.
Overall thickness	43 mm ± 2 mm
Polyethylene film	3 x 53 lm = 159 m ²
Tarfoam 1500	25 lm x 2.05 lm = 51 m ² – weight = 61,5 kg
Lumaflex	2430 mm x 138 mm x 20.5 mm delivered per 5 units = 1.68 m ² = 28 kg
Omnisports Pro	Thickness 7.70 mm Rolls 20.5 lm x 2 lm = 41 m ²
Force reduction	52 % (EN 14808)
Sliding properties	100 (EN 13036-4)
Fire rating	Euroclass: C _{fl} -S2 (EN 13501-1)
Warranty	5 years
Maintenance	According to maintenance instructions
Installation instructions	According to installation instructions
Conformity to norms	EN 14 904

We reserve the right to modify these specifications without, however, affecting their compliance with standards