

Lumaflex Resigym C

Data Sheet

Description	Polyethylene film vapor barrier. Tarfoam 1500 PU foam. Combined deformation flooring composed of 20,5 mm interlocking plywood boards to improve shock absorption. Resigym 160 floor covering: 9 mm rubber granules shock pad with 2 mm resin wear coat.
Destination	Indoor sports facilities.
Available colours	References: Beige (1001), Brown beige (1011), Saffron yellow (1017), Grey beige (1019), Azur blue (5009), Light blue (5012), Pigeon blue (5014), Sky blue (5015), Pastel blue (5024), Reseda green (6011), Pastel green (6019), Pale green (6021), Silver grey (7001), Stone grey (7030), Pepple grey (7032), Platinum grey (7036), Ocher brown (8001), Oxide red (3009), Beige red (3012), Antique pink (3014)
Overall thickness	45 mm ± 2 mm
Polyethylene film	3 x 53 lm = 159 m ²
Tarfoam 1500	37 lm x 1,5 lm = 55 m ² – weight = 66 kg
Lumaflex	2 430 mm x 138 mm x 20,5 mm delivered per 5 units = 1,68 m ² = 28 kg
Resigym 160	Thickness 11 mm
Force reduction	51 % (EN 14808)
Sliding properties	97 (EN 13036-4)
Fire rating	M3 (NFP 92506)
Warranty	5 years
Maintenance	According to maintenance instructions
Installation instructions	According to installation instructions
Conformity to norms	EN 14 904

We reserve the right to modify these specifications