

Lumaflex Training

Data Sheet

Description	Polyethylene film vapor barrier. Tarfoam 1500 PU foam. S Interlocking plywood boards, 20.5mm thick to improve shock absorption. Omnisports Training floor covering: fibreglass-stabilised vinyl floor covering with PVC foam backing. Sanitized [®] and protected with Top Clean XP [®] .
Destination	Shock absorbent sub-system combined with vinyl floor covering for sports facilities.
Available colours	Orange, red, grey, forest green, field green, royal blue, sky blue, Teal, Maple design, Beech design, Oak classic, oak gunstock.
Overall thickness	39 mm ± 2 mm
Polyethylene film	3 x 53 ml = 159 m ²
Tarfoam 1500	25 ml x 2.05 ml = 51 m ² – weight = 61.5 kg
Lumaflex	2 430 mm x 138 mm x 20.5 mm delivered per 5 units = 1.68 m ² = 28 kg
Omnisports Training	Thickness 5 mm Rolls 20.5 ml x 2 ml = 41 m ²
Shock absorption	To be defined (EN 14808)
Sliding properties	100 (EN 13036-4)
Fire rating	To be defined (EN 13501-1)
Warranty	5 years
Maintenance	According to maintenance instructions
Installation instructions	According to installation instructions
Conformity	EN 14 904

We reserve the right to modify these specifications without, however, affecting their compliance with standards