

Multiflex M

Data Sheet

Description	Polyethylene film vapor barrier. Tarfoam 1500 PU foam. Floating plywood sub-floor combined with a multiply top-layer, composed of a 3.6 mm hard-wood wear layer (3 pieces per batten) glued on offset wood lathing, high strength Proteco [®] (varnish) or unvarnished upon request.
Available wood	Beech, Oak
Destination	Indoor sports facilities
Compatible slabs	Concrete, hot-applied asphalt and asphalt screed, anhydrite screed; Any deviation of the slab must be corrected prior installation (3 mm under a 2 m straight edge).
Polyethylene film	3 x 53 ml = 159 m ²
Tarfoam 1500	25 lm x 2,05 lm = 51 m ² – weight = 61 kg
Tarflex	2440 mm x 310 mm x 9 mm – 8 units per package = 6,05 m ² = 41 kg
Boards	2525 mm x 188 mm x 13,6 mm - 6 boards per package = 2,85 m ² - 18,5 kg.
Total thickness	38 mm ± 2 mm
Sliding properties	106 (EN 13036-4)
Force reduction	52 % (EN 14808)
Fire resistance	Euroclass: C _{fi} -S1 (EN 13501-1)
Warranty	5 years
Maintenance	According to maintenance instructions
Installation instructions	According to installation instructions
Conformity	EN 14 904

We reserve the right to modify these specifications without, however, affecting their compliance with standards