

Reflex S

Data Sheet

Description	Polyethylene film vapor barrier. Tarfoam 1200 PU foam. 60 X 20,5 hemispheric battens made of 15-layer plywood, spaced 280 mm apart. 22 mm hardwood top surface pre-assembled in a press, highly resistant Proteco [®] varnish finish.
Available wood	Beech, Oak
Destination	Indoor sports facilities.
Compatible slabs	Concrete, hot-applied asphalt and asphalt screed, anhydrite screed; any deviation of the slab must be corrected prior installation (3 mm under a 2 m straight edge).
Overall thickness	55 mm ± 2 mm
Polyethylene film	3 x 53 lm = 159 m ²
Tarfoam 1200	25 lm x 2,05 lm = 51 m ² – weight = 73,4 kg
Joists	2440 mm x 60 mm x 20,5 mm - 10 units per package = 6,05 m ² – weight 19,28 kg
Boards	2400 mm x 132 mm x 22 mm- 5 boards per package = 1,58 m ² – 25,30 kg
Force reduction	50 % (EN 14808)
Sliding properties	102 (EN 13036-4)
Fire resistance	Euroclass : C _{fl} -S1 (EN 13501-1)
Warranty	5 years
Maintenance	According to maintenance instructions
Installation instructions	According to installation instructions
Conformity	EN 14 904

We reserve the right to modify these specifications without, however, affecting their compliance with standards