

## Sportable S

### Data Sheet

<b>Description</b>	Tarfoam 1200 SP reinforced PU Foam. 22 mm removable hardwood panels, pre-assembled with a double sheet press, placed on multiply battens attached underneath. Highly resistant Proteco <sup>®</sup> varnish.
<b>Available wood</b>	Beech, Maple (US version)
<b>Destination</b>	Removable wood sports floor with an integrated joist system
<b>Compatible slabs</b>	Concrete, hot-applied asphalt and asphalt screed, anhydrite screed; any deviation of the slab must be corrected prior installation (3 mm under a 2 m straight edge).
<b>Overall thickness</b>	55 mm ± 2 mm
<b>Polyethylene film</b>	53 lm x 3 lm = 159 m <sup>2</sup>
<b>Tarfoam 1200 SP</b>	25 lm x 2.05 lm = 51 m <sup>2</sup>
<b>Full panel</b>	2380 mm x 663 mm - 46 panels per package
<b>Half panel</b>	1190 mm x 663 mm - 46 panels per package
<b>Threshold</b>	Inox, Aluminium (US version)
<b>Force reduction</b>	55 % (EN 14808)
<b>Sliding properties</b>	102 (EN 13036-4)
<b>Fire resistance</b>	Euroclass: C <sub>fi</sub> -S1 (EN 13501-1)
<b>Warranty</b>	5 years
<b>Maintenance</b>	According to maintenance instructions
<b>Installation instructions</b>	According to installation instructions
<b>Conformity</b>	EN 14 904

*We reserve the right to modify these specifications without, however, affecting their compliance with standards*